
# Comfort and Performance for your Active Lifestyle







The Victory® 9.2 series of mobility scooters offer a perfect balance of style, comfort and performance for your active lifestyle. The Victory® 9.2 features one-hand feather-touch disassembly, wraparound delta tiller, 300 lb. weight capacity, a per charge range up to 17.5 miles and a maximum speed up to 5.6 mph. Standard features include, 9" solid tires, frosted LED headlights and a front basket. Available in Ocean Blue and Candy Apple Red.













## Specifications 3W: S6092 4W: S7092

Weight Capacity	300 lbs.
Maximum Speed <sup>1</sup>	Up to 5.6 mph
Ground Clearance <sup>3</sup>	1.75" at motor
Turning Radius <sup>3</sup>	3W: 40.25" 4W: 52"
Overall Length <sup>3</sup>	3W: 43.5" 4W: 46"
Overall Width³	22.25"
Seat-to-Ground Height	21.5" – 24.5"
Seat-to-Deck Height	15.25" – 18.25"
Front Tires	3W: 3" x 8" solid 4W: 3" x 9" solid
Rear Tires	3" x 9" solid
Suspension	N/A
Range Per Charge <sup>1,2</sup>	3W: Up to 17.5 miles 4W: Up to 16.5 miles
Total Weight Without Batteries <sup>3,7</sup>	3W: 125.75 lbs. 4W: 136 lbs.
Heaviest Piece When Disassembled <sup>3</sup>	3W: 51.75 lbs. (front section) 4W: 61.5 lbs. (front section)
Standard Seating	Foldable molded plastic Weight: 28.5 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drive System	Rear-wheel drive, sealed transaxle with 24-volt DC motor
Dual Braking System	Regenerative and electromechanical
Battery Requirements <sup>3,4,5</sup>	Size: (2) U-1 standard Weight: 24.5 lbs. each
Battery Charger	3.5-amp, off-board
Colors	

Candy Apple Red Ocean Blue

## HCPCS code: K0800 (Group 1, Standard)

- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of +10%, -5%
- 2 Tested in accordance with ANSI/RESNA, WC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance Test conducted at maximum weight capacity.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 AGM or gel cell type required
- Battery weight may vary based on battery manufacturer.
- 6 Includes standard seat weight.

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining the appropriate billing codes when submitting for

#### **Features**

- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- New under-tiller puddle light improves visibility to USB charging port and tiller-mounted storage
- Integrated storage/cup holder in tiller
- New ambient voltmeter adjusts brightness to suit your environment
- Integrated USB mobile device charging port in tiller
- New frosted LED headlights and low-mounted LED pathway light brightens your route
- Delta tiller with wraparound handles
- Pinchless hinge seat with swivel and sliders for increased comfort. Available in sizes 18" x 17" and 20" x 18"
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port

### Accessories

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 50", 60", 70" Lap belt
- Oxygen tank holder

- Quad cane holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- Wishbone crutch holder

## Military Patches





Pride offers a variety of lifts to transport your mobility product with ease. To find a compatible lift for your vehicle and mobility product, use our new Lift Finder application at pridemobility.com/lift-finder/

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.









